



TW2000S-60W-70 DUPLEX BOOSTER PUMP SYSTEM MODULAR FRAME

The *TW2000S-60W-70 Duplex Booster Pump System* is equipped with centrifugal pumps regulated by variable frequency drives that control the pump to maintain constant pressure regardless of varying demand or fluctuating incoming pressure. This system will supply *60 GPM with a 70 PSI overboost*.

System is built on a MODULAR frame for ease of transport and installation.

VFD drives will ALTERNATE lead pump every 24 hours of run time and 2nd pump remains in standby until needed.

Lead-Free (Wetted) components:

- Centrifugal Pumps: Cast Iron [SS Option]
- Relief valves: Lead Free Brass or SS
- Pressure Gauges: Stainless Steel
- Transducer: Stainless Steel
- Check valves: Lead Free Brass
- Ball Valves: Lead Free Brass
- Manifolds: Lead Free Type L Copper
- Fittings: Lead Free Copper or SS

* All lead-free brass shall contain <.25% Pb



*All parts shown included
Actual system components may vary
Some assembly required*

Technical Specifications:

- Pumps:** Walrus [8T-5K]
- Controllers:** Yaskawa or equal
- Flow Rate:** 60 GPM (30 GPM per pump)
- Boost:** 70 Overboost
- Set Pressure:** 65 PSI (specify when ordering)
- Horse Power:** 2 HP per pump
- Manifolds:** 3 inch Type L Copper
- Tank:** Watts PLT-35 (14 Gal)
- Frame Size:** 32" W x 54" H x 34" D
- Power Options:** Two Independent circuits required
208-220V/1PH or
208-220V/3PH or
360-480V/3PH
Specify when ordering

Performance curve for each pump

